



anchor o.d. [in.]	1/4	3/8	1/2	5/8	3/4	1				
d <sub>bit</sub> [in]	1/4	3/8	1/2	5/8	3/4	1				
min. h <sub>o</sub> [in]	2	2-5/8	2-5/8	4	3-7/8	4-3/4	4-1/2	5-3/4	5	6-3/4
min. h <sub>nom</sub> [in]	1-3/4	2-3/8	2-1/4	3-5/8	3-1/2	4-3/8	4-1/4	5-5/8	4-5/8	6-3/8
min. h <sub>ef</sub> [in]	1-1/2	2	2	3-1/4	3-1/8	4	3-3/4	5	4	5-3/4
T <sub>inst</sub> [ft-lb]	4	20	40	60	110	150				
d <sub>h</sub> [in]	5/16	7/16	9/16	11/16	13/16	1-1/8				
wrench size [in]	7/16	9/16	3/4	15/16	1-1/8	1-1/2				

Use only carbide-tipped masonry drill bits complying with ANSI B212.15-1994

Hilti Inc. (US), [www.us.hilti.com](http://www.us.hilti.com), 1 800 879 8000  
 Hilti Co. (Canada), [www.ca.hilti.com](http://www.ca.hilti.com), 1 800 363 4458